



simply
elegant

technologically
efficient

High energy-efficient extractors

for bathroom, toilet and kitchen with perimeter extraction and **removable white glass extra-flat front.**



E-100 GTH



the E-100 series

The new E-100 series of extractors has been created with the desire to set a new standard in the market, combining efficiency and elegance to offer extraction units with high levels of energy saving, extraction capacity, durability and silence.

A close-up, angled view of a silver-colored metal panel, likely part of an extractor unit. The panel has horizontal lines and the "cataC" logo is visible in the lower right corner.

cataC

E-100 G
E-100 GT



E-100 GTHygro

Adjustable humidity detector between 40% and 90%.

Adjustable electronic timer between 0 and 15 minutes.
2 speeds.

Temperature and relative humidity indicator.



E-100 GTTimer

Adjustable electronic timer between 3 and 15 minutes.



E-100 GStandard

Activated with the light switch.



Easy to remove and clean

Using a single tool, supplied with the extractor, in just a few seconds you can easily remove the glass front to clean it just by running a damp cloth over it. The same tool allows you to adjust the timer (E-100 GTH and E-100 G) and the humidistat (E-100 GTH).

High capacity and low consumption

With a high extraction flow of 90m³/h, the absorbed power is just 8W.



Extremely silent

The quality of the components and their mechanical design allow a sound pressure level of just 31 dB(A) at 2600 r.p.m.



Perimeter extraction system

Thanks to the perimeter extraction system, the E-100 series prevents the accumulation of dirt found in conventional extractors.

Adaptable to every need

The **Hygro** model (E-100 GTH) is fitted with a 2-speed motor:

1st speed: adjustable between two extraction levels prior to installation.

2nd speed: activated on turning the light on, and on activating the humidistat or the timer.

Safe and durable

The E-100 series is fitted with 220-240 50Hz, IP-44 protection and Class B motors.

The turbine and body of the extractor are made of high-performance plastic.

A non-return valve can be fitted as optional.



cata

characteristics




E-100 G



E-100 GT



E-100 GTH

Code	00900000	00900100	00900200		
Pipe Diameter (mm)	100	100	100		
Voltage (V)	220-240	220-240	220-240		
Speeds (r.p.m.)	single	single	1st speed	1st speed	2nd speed
	2600	2600	1100*	1800**	2600
Absorbed power (W)	8	8	4	5	8
Maximum Flow (m³/h – l/s)	90-25	90-25	36-10	58-16	90-25
Sound Pressure Level dB(A)	31	31	17	21	31
Timer (m)	-	3-15	0-15		
Humidistat (%)	-	-	40-95		
Dimensions (mm)					

* continuous extraction level indicated for installation in bathrooms

** continuous extraction level indicated for installation in kitchens